

ALLTRADES



TRAILERS

YOUR EQUIPMENT OUR SOLUTIONS


Ph: 1300 611 301

EXCAVATOR TRAILERS

ALL-TOW 2200

2.2 Ton

The All-Tow 2200 Trailer is built to suit machines with an **operating weight of 1800kg or less including buckets.**



SPECIFICATIONS

- » ATM: 2200Kg
- » Chassis Main Beam Size: 100mm x 50mm x 3mm
- » Trailer Weight: 400Kg
- » Trailer OA Length: 4100mm
- » Trailer OA Width: 1870mm
- » Distance Between Guards: 1350mm
- » Number of Axles: 2
- » Axle Type: 45mm x 45mm Solid
- » Wheel Size: 14" Light Truck (Load Rated)
- » Stud Pattern: Ford
- » Lighting: LED Lights 12/24
- » Chassis Assembly: Welded
- » Stand Up Ramp Length: 1360mm
- » Stand Up Ramp Width: 370mm
- » Stand Up Ramps Fixed
- » Brake Type: Mech Brake 10in Disc - 1 Axle Braked
- » Suspension: AL-KO Rock Roller
- » Hitch 50mm Ball

FEATURES

- » Galvanised Steel Subframe
- » Aluminium Deck
- » Aluminium Ramps
- » 300mm Track Deck
- » Powder Coated Guards
- » Plug 'n' Play Lights
- » (TILT Trailer)

CUSTOM MADE TRAILERS

**Proudly Built
in Australia**



Site Address

Unit 24/3-9 Octal Street
Yatala, QLD 4207 Australia

Postal Address

PO Box 1049
Oxenford, QLD 4210

Contact Details

P: 1300 611 301 | M: 0434 615 495
E: sales@alltradetrailers.com.au

