

MINI LOADER TRAILERS

ALL-TOW 2800L 2.8 Ton



The All-Tow 2800L Trailer is built to suit machines with an **operating weight of 2230kg or less including buckets.**



SPECIFICATIONS

- » ATM: 3000Kg
- » Chassis Main Beam Size: 100mm x 50mm x 4mm
- » Trailer Weight: 670Kg
- » Trailer OA Length: 5200mm
- » Trailer OA Width: 2100mm
- » Distance Between Guards: 1530mm
- » Number of Axles: 2
- » Axle Type: 50mm x 50mm 65mm Drop
- » Wheel Size: 14" Light Truck (Load Rated)
- » Stud Pattern: Ford
- » Lighting: LED Lights 12/24
- » Chassis Assembly: Welded
- » Stand Up Ramp Length: 1455mm
- » Stand Up Ramp Width: 370mm
- » Stand Up Ramps Adjustable
- » Brake Type: 10" Electric Braked
- » Suspension: AL-KO Rock Roller
- » Hitch 50mm Ball

FEATURES

- » Galvanised Steel Subframe
- » Aluminium Deck
- » Aluminium Ramps
- » 380mm Rear Load Height
- » Powder Coated Guards
- » Plug 'n' Play Lights
- » Fixed Drawbar
- » Full Floor

Optional Extras

- » Auger Carrier
- » Trencher Carrier
- » Spreader Bar Holder
- » Drill Holders
- » And More

CUSTOM MADE TRAILERS

Proudly Built
in Australia



Site Address

22 Blue Rock Drive,
Yatala, QLD 4207 Australia

Postal Address

PO Box 457
Ormeau, QLD 4208

Contact Details

P: 1300 611 301 | M: 0434 615 495
E: sales@alltradetrailers.com.au

