

ALLTRADES



TRAILERS

YOUR EQUIPMENT OUR SOLUTIONS


Ph: 1300 611 301

EXCAVATOR TRAILERS

ALL-TOW 4500

4.5 Ton

The All-Tow 4500 Trailer is built to suit machines with an operating weight of 3650kg or less including buckets.



SPECIFICATIONS

- » ATM: 4499Kg
- » Chassis Main Beam Size: 125mm x 65mm x 8mm PFC
- » Trailer Weight: 900Kg
- » Trailer OA Length: 5100mm
- » Trailer OA Width: 2450mm
- » Distance Between Guards: 1800mm
- » Number of Axles: 2
- » Axle Type: 65mm x 65mm
- » Wheel Size: 16" Light Truck (Load Rated)
- » Stud Pattern: LC
- » Lighting: LED Lights 12/24
- » Chassis Assembly: Welded
- » Stand Up Ramp Length: 1455mm
- » Stand Up Ramp Width: 500mm
- » Stand Up Ramps Fixed
- » Brake Type: 12" Electric Braked
- » Suspension: AL-KO Rock Roller
- » Hitch 70mm Ball or Pintle

FEATURES

- » Galvanised Steel Subframe
- » Aluminium Deck
- » Aluminium Ramps
- » 500mm Track Deck
- » Powder Coated Guards
- » Plug 'n' Play Lights
- » Fixed Drawbar

Optional Extras

- » Drill Holders
- » Auger Driver Holder
- » Hammer Rack
- » Bucket Rack
- » And More

CUSTOM MADE TRAILERS

Proudly Built
in Australia



Site Address

22 Blue Rock Drive,
Yatala, QLD 4207 Australia

Postal Address

PO Box 1049
Oxenford, QLD 4210

Contact Details

P: 1300 611 301 | M: 0434 615 495
E: sales@alltradetrailers.com.au

